

20079742-021902

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25

**I CLAIM:**

1. A cargo carrier comprising:  
a frame having a front edge with a trailer hitch  
connection;  
a left and a right jack assembly;  
each said jack assembly having a riser body; and said  
frame having a left and a right edge each having  
a jack connector assembly for removable  
attachment to the respective riser body.
2. The cargo carrier of claim 1, wherein the left and  
right jack assemblies each have a caster, thereby enabling  
the jack assemblies to be connected to the frame and to roll  
the frame in and out of a vehicle's receiving hitch.
3. The cargo carrier of claim 1 wherein the jack  
connector assemblies each comprise a bracket longitudinally  
alignable with the respective left and right edge of the  
frame, said bracket having a quick disconnect mechanism to  
the frame edge.
4. The cargo carrier of claim 3, wherein each quick  
disconnect mechanism is a locking pin received thru both the  
frame and the bracket.

1        5.    The cargo carrier of claim 4, wherein the frame  
2 further comprises a square tube construction, and the  
3 bracket has a C shape to engage a side of the square tube.

4  
5        6.    The cargo carrier of claim 3, wherein the left and  
6 right jack assemblies each further comprise a caster.

7  
8        7.    The cargo carrier of claim 3, wherein the trailer  
9 hitch connection further comprises a removable male hitch  
10 shaft which is adapted to fit into a vehicle hitch, and the  
11 frame further comprising a receiving hitch tube, thereby  
12 enabling the male hitch shaft to be connected to the vehicle  
13 hitch and then receive the receiving hitch tube in a loading  
14 operation of the frame onto the vehicle.

15  
16        8.    The cargo carrier of claim 1, wherein the frame  
17 front edge further comprises a left and right stabilizer bar  
18 protruding forward for contact with a vehicle bumper.

19        9.    A cargo carrier comprising:  
20        a frame having a front edge with a trailer hitch  
21        connection; and  
22        said frame having a left and a right edge each with a  
23        removable connector for removable attachment to a jack.

24       10.    A cargo carrier comprising:

20054201 24767007

1 a frame having a front edge with a trailer hitch  
2 connection;  
3 a left and a right jack assembly;  
4 each said jack assembly having a riser body;  
5 said frame having a left and a right edge each having  
6 a jack connector assembly for removable  
7 attachment to the respective riser body; and  
8 wherein the jack connector assemblies each comprise a  
9 bracket longitudinally alignable with the  
10 respective left or right edge of the frame, said  
11 bracket having a quick disconnect mechanism to  
12 the frame edge.

13  
14 11. The cargo carrier of claim 1, wherein the jack  
15 connector assembly further comprises a vertical column  
16 mounted to the left and the right edge of the frame, said  
17 vertical column having a male connector to receive a female  
18 connector on the jack assembly.

19  
20 12. A cargo carrier comprising: a frame having a front  
21 edge with a trailer hitch connection; a left and a right  
22 jack assembly; each said jack assembly having a riser body;  
23 said frame having a left and a right edge each having a jack  
24 connector assembly for removable attachment to the removable  
25 attachment to the respective riser body; and wherein the

10079742-021902  
2005T20-242520T

1 jack connector assembly further comprises a vertical column  
2 mounted to the left and the right edge of the frame, said  
3 vertical column having a male connector to receive a female  
4 connector on the jack assembly.

5

6 13. A cargo carrier comprising; a frame means  
7 functioning to support a cargo box; said frame means having  
8 a front edge with a trailer hitch means functioning to  
9 connect to a vehicle hitch; a left and a right jack assembly  
10 means functioning to lift the frame means to a level for  
11 mounting to the vehicle hitch; said frame means having a  
12 left and a right edge means each having a jack connector  
13 means functioning to removably connect to the jack assembly  
14 means.

15

16 14. The cargo carrier of claim 13, wherein the left and  
17 the right jack assemblies each further comprise a wheel  
18 means functioning to enable the frame and cargo box to be  
19 rolled to and from the vehicle hitch.

20

21 15. The cargo carrier of claim 14, wherein the trailer  
22 hitch means further comprises a removable male hitch shaft  
23 means functioning to attach to the vehicle hitch and to a  
24 frame female shaft receiver, thereby enabling the cargo box

1 and frame to be rolled into the removable male hitch shaft  
2 when it is mounted to the vehicle hitch.

3

4 16. The cargo carrier of claim 15 wherein the front  
5 edge further comprises a left and a right stabilizer means  
6 functioning to contact the vehicle under load and reduce  
7 movement of the frame means.

8

9

10

2025 FEB 20 24 46 00